

# Performance Pinball - Playfield Jacks

## User guide

**PRECAUTION** – As the playfield overhangs the front of the cabinet during use, please make sure your work area is clear and take caution not to dislodge the front playfield section while working

### Step 1.

1. Power OFF the machine
2. Remove lockdown bar and glass, store in a safe place
3. Lift the playfield up and forward with playfield rails resting on the lockbar receiver
4. Continue pulling the playfield assembly forward to position the rail support bumpers so that they sit inside the lockbar/cabinet recess area as seen on page 2
5. **Ensure the rubber bumpers** are contained securely between the metal lip and front cabinet so that they are captured, unable to move forward or rearward
6. **These steps are REQUIRED** in order to lock in the playfield and ensure it is stable and secure before installing Playfield Jacks



### Step 2.

7. With each L/R Playfield Jack staged on its rail near the rear of the game, use one hand to lift the center rear of the playfield or playfield handle (if equipped) reposition and seat the playfield jack onto the side-rail/cabinet, resting under and supporting the playfield

8. While continuing to support the playfield repeat for the opposite side and re-check your overall playfield positioning to ensure it is safe to work
9. Once work has completed reset playfield in reverse order

**Suggested SAFETY measure**

For added safety it is recommended to utilize ratcheting clamps (as seen below) to further secure the playfield rails to the cabinet on the front lockbar area of the machine while in service.

